

Bloczki Classic Bullet i Dinghy



113



092
109
132



088
106
131

Wycięcie
088, 106 - 3/4" (19 mm) x 1 1/4" (44 mm)
131 - 1 5/16" (24 mm) x 2 3/16" (56 mm)



089
134

Wycięcie
089 - 1 9/16" (21 mm) x 2 5/8" (67 mm)
134 - 1 9/16" (24 mm) x 3 11/16" (94 mm)



096
108
222

096, 108 - 1 1/16" (30 mm)
222 - 1 1/16" (33 mm)



220
223

220 - 1 15/16" (49 mm)
223 - 2 1/4" (57 mm)



287
288

Wycięcie
287, 288 - 3/4" (19 mm) x 1 1/4" (44 mm)



289

Wycięcie
289 - 3/4" (19 mm) x 2 5/8" (67 mm)



046

Wycięcie
1 1/16" (27 mm)
x 2 11/16" (68 mm)

Zach Railey, Kieler Woch 2010 — FRIED ELLIOTT/friedbits.com photo

Nr kat.	Opis	Rolka Ø		Długość		Waga		Maks. lina Ø		Przetyczka szekli Ø		Maks. siła robocza		Siła zrywająca	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
Bullet															
088	Przejście pokładowe*	1 1/8	29	3	76	1.25	35	5/16	8	—	—	300	136	2000	907
089	Wpuszczany podwójny*	1 1/8	29	3 3/4	95	1.75	50	5/16	8	—	—	400	181	2000	907
092	Leżący**	1 1/8	29	2 7/8	73	1.25	35	5/16	8	—	—	300	136	2000	907
096	Skrzynkowy**	1 1/8	29	1 1/2	38	1.5	43	5/16	8	—	—	300	136	2000	907
106	Przejście pokładowe do stalówki*	1 1/8	29	3	76	1.25	35	5/16	8	—	—	500	227	2000	907
108	Skrzynkowy do stalówki**	1 1/8	29	1 1/2	38	1.5	43	5/16	8	—	—	500	227	2000	907
109	Leżący do stalówki**	1 1/8	29	2 7/8	73	1.25	35	5/16	8	—	—	500	227	2000	907
113	Leżący obrotowy**	1 1/8	29	1 1/8	29	1	28	5/16	8	—	—	300	136	2000	907
220	Skrzynkowy podwójny**	1 1/8	29	1 1/2	38	2.25	64	5/16	8	—	—	400	181	2000	907
287	Przejście pokładowe**	1 1/8	29	3	76	1.25	35	5/16	8	—	—	300	136	2000	907
288	Wpuszczany na stalówkę**	1 1/8	29	3	76	1.5	43	5/16	8	—	—	400	181	2000	907
289	Podwójne wyjście masztowe**	1 1/8	29	3 3/4	95	2	60	5/16	8	—	—	400	181	2000	907
Big Bullet															
131	Przejście pokładowe*	1 1/2	38	3 1/2	89	2.25	64	3/8	10	—	—	300	136	2000	907
132	Leżący*	1 1/2	38	3 1/2	89	2	57	3/8	10	—	—	300	136	2000	907
134	Wpuszczany podwójny*	1 1/2	38	5	127	3.25	92	3/8	10	—	—	600	272	2000	907
222	Skrzynkowy**	1 1/2	38	2 1/4	57	2.5	71	3/8	10	—	—	300	136	2000	907
223	Skrzynkowy podwójny**	1 1/2	38	2 1/4	57	3.25	92	3/8	10	—	—	600	272	2000	907
Dinghy															
046	Przejście pokładowe‡	1 3/4	44	3	76	4	113	3/8	10	—	—	350	159	2000	907

*Śruby montażowe FH #10 (5 mm) **Śruby montażowe RH #10 (5 mm) ‡Śruby montażowe RH #8 (4 mm) Skontaktuj się z Harken® by uzyskać informacje o innych bloczkach 1 3/4" (44 mm)